

RTU3-I.250-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1100			879 / 0.39	1064 / 0.63	1220 / 0.90	1360 / 1.20	1486 / 1.51	1603 / 1.85	1711 / 2.19
1650			915 / 0.51	1094 / 0.81	1248 / 1.13	1384 / 1.48	1508 / 1.84	1622 / 2.22	1730 / 2.63
2200			968 / 0.66	1135 / 1.01	1284 / 1.39	1418 / 1.79	1540 / 2.20	1652 / 2.64	1757 / 3.09
2750		895 / 0.50	1047 / 0.85	1193 / 1.24	1330 / 1.67	1457 / 2.12	1576 / 2.59	1686 / 3.07	1790 / 3.58
3300	882 / 0.38	1018 / 0.71	1146 / 1.09	1271 / 1.52	1392 / 1.98	1510 / 2.48	1622 / 3.00	1728 / 3.55	1829 / 4.11
3850	1029 / 0.60	1147 / 0.97	1258 / 1.40	1367 / 1.86	1474 / 2.37	1579 / 2.91	1682 / 3.47	1781 / 4.06	
4400	1176 / 0.90	1281 / 1.32	1379 / 1.78	1475 / 2.28	1570 / 2.83	1664 / 3.40	1756 / 4.01	1847 / 4.64	
4950	1323 / 1.28	1417 / 1.75	1505 / 2.25	1591 / 2.79	1676 / 3.37	1761 / 3.99	1844 / 4.62		
5500	1469 / 1.76	1555 / 2.27	1635 / 2.82	1714 / 3.40	1791 / 4.02	1868 / 4.67			
6050	1616 / 2.34	1695 / 2.90	1768 / 3.49	1841 / 4.12					
6600	1763 / 3.04	1835 / 3.64							

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.