

RTU3-I.300-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			901 / 0.47	1083 / 0.76	1238 / 1.06	1375 / 1.39	1500 / 1.75	1615 / 2.11	1722 / 2.50	1823 / 2.90
2050			946 / 0.61	1118 / 0.95	1269 / 1.31	1405 / 1.69	1528 / 2.09	1641 / 2.51	1748 / 2.95	1847 / 3.40
2600		858 / 0.45	1017 / 0.78	1169 / 1.16	1310 / 1.57	1440 / 2.01	1561 / 2.46	1672 / 2.94	1777 / 3.43	
3150	831 / 0.31	976 / 0.63	1110 / 0.99	1241 / 1.41	1367 / 1.87	1487 / 2.35	1601 / 2.86	1710 / 3.39	1812 / 3.93	
3700	976 / 0.50	1102 / 0.86	1218 / 1.27	1331 / 1.73	1442 / 2.22	1551 / 2.74	1655 / 3.29	1758 / 3.87	1855 / 4.46	
4250	1121 / 0.76	1233 / 1.17	1335 / 1.62	1434 / 2.11	1533 / 2.64	1630 / 3.20	1725 / 3.79	1819 / 4.41		
4800	1266 / 1.10	1366 / 1.55	1459 / 2.05	1547 / 2.58	1635 / 3.14	1722 / 3.74	1808 / 4.36			
5350	1411 / 1.52	1502 / 2.02	1586 / 2.56	1667 / 3.13	1747 / 3.74	1825 / 4.37				
5900	1556 / 2.04	1639 / 2.59	1717 / 3.17	1791 / 3.79	1864 / 4.43					
6450	1701 / 2.66	1778 / 3.26	1850 / 3.90							
7000	1846 / 3.40									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.