

RTU3-I.300HE-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			916 / 0.49	1097 / 0.78	1250 / 1.09	1386 / 1.42	1511 / 1.78	1625 / 2.15	1732 / 2.54	1832 / 2.94
2000			969 / 0.64	1139 / 0.98	1288 / 1.34	1420 / 1.72	1542 / 2.12	1656 / 2.54	1761 / 2.98	1857 / 3.42
2500		877 / 0.49	1040 / 0.83	1193 / 1.21	1334 / 1.62	1463 / 2.05	1581 / 2.50	1691 / 2.97	1795 / 3.45	
3000	849 / 0.37	991 / 0.69	1130 / 1.06	1264 / 1.49	1393 / 1.94	1514 / 2.42	1628 / 2.92	1734 / 3.44	1833 / 3.96	
3500	990 / 0.58	1112 / 0.95	1232 / 1.36	1350 / 1.82	1466 / 2.32	1577 / 2.84	1684 / 3.39	1786 / 3.95		
4000	1132 / 0.87	1239 / 1.28	1344 / 1.73	1449 / 2.23	1552 / 2.76	1653 / 3.33	1751 / 3.92	1847 / 4.53		
4500	1273 / 1.24	1369 / 1.69	1462 / 2.19	1556 / 2.72	1648 / 3.29	1740 / 3.90	1830 / 4.53			
5000	1414 / 1.70	1501 / 2.20	1586 / 2.74	1670 / 3.31	1754 / 3.92	1837 / 4.56				
5500	1555 / 2.26	1634 / 2.81	1712 / 3.39	1789 / 4.00	1865 / 4.65					
6000	1697 / 2.94	1769 / 3.53	1840 / 4.15							
6500	1838 / 3.73									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.