

RTU3-I.400-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900			914 / 0.54	1092 / 0.86	1246 / 1.21	1384 / 1.58	1508 / 1.96	1624 / 2.37	1730 / 2.78	1832 / 3.22
2410			966 / 0.66	1127 / 1.02	1274 / 1.42	1408 / 1.84	1530 / 2.27	1644 / 2.72	1750 / 3.19	1851 / 3.68
2920		893 / 0.48	1038 / 0.81	1179 / 1.21	1313 / 1.64	1439 / 2.10	1558 / 2.58	1669 / 3.08	1774 / 3.61	
3430	860 / 0.30	1000 / 0.63	1126 / 1.01	1249 / 1.43	1369 / 1.89	1484 / 2.38	1595 / 2.91	1701 / 3.46	1802 / 4.02	
3940	988 / 0.46	1112 / 0.83	1224 / 1.24	1332 / 1.69	1439 / 2.18	1543 / 2.71	1645 / 3.27	1744 / 3.85	1840 / 4.46	
4450	1116 / 0.66	1228 / 1.08	1329 / 1.53	1426 / 2.01	1521 / 2.53	1615 / 3.08	1708 / 3.67	1799 / 4.29		
4960	1243 / 0.91	1346 / 1.38	1438 / 1.87	1526 / 2.39	1613 / 2.94	1698 / 3.52	1783 / 4.14	1867 / 4.79		
5470	1371 / 1.22	1465 / 1.74	1550 / 2.27	1631 / 2.83	1711 / 3.41	1789 / 4.03	1866 / 4.67			
5980	1499 / 1.60	1586 / 2.16	1665 / 2.74	1740 / 3.33	1814 / 3.95					
6490	1627 / 2.04	1707 / 2.66	1781 / 3.27	1852 / 3.91						
7000	1754 / 2.57	1830 / 3.22								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.