

RTU3-I.400HE-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900			963 / 0.62	1134 / 0.95	1284 / 1.30	1417 / 1.67	1538 / 2.06	1652 / 2.47	1758 / 2.90	1855 / 3.34
2360		855 / 0.46	1026 / 0.79	1184 / 1.16	1326 / 1.55	1456 / 1.97	1575 / 2.41	1686 / 2.87	1789 / 3.34	
2820	809 / 0.32	958 / 0.63	1105 / 1.00	1246 / 1.41	1378 / 1.85	1502 / 2.31	1617 / 2.80	1725 / 3.30	1826 / 3.81	
3280	941 / 0.51	1069 / 0.86	1197 / 1.26	1322 / 1.71	1442 / 2.19	1557 / 2.69	1668 / 3.22	1771 / 3.77		
3740	1072 / 0.75	1186 / 1.14	1298 / 1.58	1409 / 2.07	1518 / 2.58	1624 / 3.13	1727 / 3.70	1825 / 4.29		
4200	1204 / 1.07	1306 / 1.50	1406 / 1.98	1505 / 2.49	1604 / 3.05	1700 / 3.63	1795 / 4.24			
4660	1336 / 1.46	1427 / 1.93	1518 / 2.45	1608 / 3.00	1697 / 3.59	1786 / 4.21				
5120	1468 / 1.94	1551 / 2.45	1634 / 3.01	1716 / 3.60	1798 / 4.22					
5580	1600 / 2.51	1676 / 3.06	1752 / 3.66	1828 / 4.29						
6040	1732 / 3.18	1802 / 3.78								
6500	1864 / 3.96									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 800 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 800 to 1870.