

RTU4-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500		656 / 0.21	884 / 0.45	1068 / 0.73	1222 / 1.03	1360 / 1.35	1484 / 1.69	1597 / 2.04	1705 / 2.42	1805 / 2.81
2000		717 / 0.27	917 / 0.55	1092 / 0.88	1245 / 1.24	1381 / 1.61	1505 / 2.00	1618 / 2.40	1724 / 2.82	1823 / 3.25
2500	615 / 0.11	801 / 0.36	969 / 0.67	1127 / 1.03	1273 / 1.44	1405 / 1.86	1527 / 2.30	1640 / 2.76	1746 / 3.23	1845 / 3.71
3000	738 / 0.18	898 / 0.47	1040 / 0.81	1179 / 1.21	1312 / 1.64	1437 / 2.11	1554 / 2.60	1666 / 3.11	1769 / 3.63	1868 / 4.17
3500	861 / 0.29	1002 / 0.62	1126 / 0.99	1247 / 1.41	1366 / 1.88	1481 / 2.38	1591 / 2.90	1697 / 3.46	1798 / 4.03	
4000	984 / 0.43	1110 / 0.81	1221 / 1.21	1328 / 1.66	1434 / 2.15	1538 / 2.68	1639 / 3.24	1738 / 3.83	1834 / 4.44	
4500	1107 / 0.61	1221 / 1.04	1322 / 1.48	1419 / 1.96	1514 / 2.48	1607 / 3.03	1700 / 3.62	1791 / 4.23		
5000	1230 / 0.84	1335 / 1.31	1427 / 1.79	1516 / 2.31	1602 / 2.85	1687 / 3.43	1771 / 4.04	1855 / 4.68		
5500	1353 / 1.12	1450 / 1.63	1535 / 2.16	1617 / 2.71	1696 / 3.29	1774 / 3.89	1851 / 4.53			
6000	1476 / 1.45	1566 / 2.01	1646 / 2.58	1722 / 3.17	1795 / 3.78	1867 / 4.42				
6500	1599 / 1.84	1683 / 2.45	1758 / 3.07	1829 / 3.70						

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 500 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 500 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 500 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 500 to 1870.