

**RTU4-E.1204-22-FA**

| CFM  | Static Pressure in Inches W.G. |             |             |             |             |             |             |             |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
|      | 0.000                          | 0.500       | 1.000       | 1.500       | 2.000       | 2.500       | 3.000       | 3.500       |
|      | RPM/BHP                        | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     |
| 3750 |                                | 1064 / 0.73 | 1181 / 1.13 | 1294 / 1.56 | 1405 / 2.04 | 1514 / 2.55 | 1619 / 3.10 | 1721 / 3.67 |
| 4025 | 1001 / 0.47                    | 1124 / 0.85 | 1235 / 1.26 | 1341 / 1.71 | 1446 / 2.21 | 1548 / 2.73 | 1649 / 3.30 | 1746 / 3.88 |
| 4300 | 1069 / 0.57                    | 1186 / 0.97 | 1291 / 1.41 | 1391 / 1.88 | 1489 / 2.39 | 1587 / 2.93 | 1682 / 3.50 | 1775 / 4.11 |
| 4575 | 1138 / 0.68                    | 1248 / 1.11 | 1348 / 1.57 | 1443 / 2.06 | 1536 / 2.58 | 1628 / 3.14 | 1719 / 3.73 | 1808 / 4.35 |
| 4850 | 1206 / 0.82                    | 1310 / 1.27 | 1406 / 1.75 | 1496 / 2.26 | 1585 / 2.80 | 1672 / 3.37 | 1759 / 3.98 | 1843 / 4.61 |
| 5125 | 1274 / 0.96                    | 1375 / 1.44 | 1465 / 1.94 | 1552 / 2.47 | 1636 / 3.03 | 1719 / 3.62 | 1801 / 4.24 |             |
| 5400 | 1343 / 1.12                    | 1438 / 1.63 | 1525 / 2.15 | 1608 / 2.70 | 1689 / 3.28 | 1768 / 3.89 | 1846 / 4.52 |             |
| 5675 | 1411 / 1.31                    | 1503 / 1.84 | 1586 / 2.38 | 1665 / 2.95 | 1742 / 3.55 | 1818 / 4.17 |             |             |
| 5950 | 1480 / 1.50                    | 1567 / 2.06 | 1648 / 2.63 | 1724 / 3.22 | 1798 / 3.84 |             |             |             |
| 6225 | 1548 / 1.72                    | 1633 / 2.30 | 1710 / 2.90 | 1783 / 3.51 | 1854 / 4.15 |             |             |             |
| 6500 | 1617 / 1.96                    | 1698 / 2.57 | 1772 / 3.19 | 1843 / 3.82 |             |             |             |             |

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 1000 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 1000 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 1000 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 1000 to 1870.