

RTU4-E.1204-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3750	670 / 0.25	803 / 0.59	928 / 1.00	1050 / 1.48	1165 / 2.00	1273 / 2.55	1375 / 3.13	1470 / 3.73	1561 / 4.35
4175	746 / 0.34	866 / 0.71	980 / 1.15	1091 / 1.65	1198 / 2.20	1301 / 2.78	1398 / 3.40	1491 / 4.04	1580 / 4.70
4600	821 / 0.45	932 / 0.86	1036 / 1.32	1138 / 1.84	1238 / 2.42	1334 / 3.03	1427 / 3.68	1516 / 4.35	
5025	897 / 0.59	999 / 1.03	1095 / 1.52	1189 / 2.06	1282 / 2.66	1372 / 3.30	1460 / 3.97	1545 / 4.68	
5450	973 / 0.75	1068 / 1.22	1157 / 1.74	1244 / 2.31	1330 / 2.93	1415 / 3.59	1498 / 4.29	1579 / 5.02	
5875	1049 / 0.94	1137 / 1.45	1221 / 1.99	1302 / 2.59	1383 / 3.23	1462 / 3.91	1540 / 4.64		
6300	1125 / 1.16	1207 / 1.70	1286 / 2.28	1362 / 2.90	1438 / 3.56	1512 / 4.27			
6725	1200 / 1.41	1278 / 1.98	1352 / 2.59	1424 / 3.24	1495 / 3.93	1566 / 4.66			
7150	1276 / 1.70	1350 / 2.30	1419 / 2.94	1488 / 3.62	1555 / 4.34				
7575	1352 / 2.02	1422 / 2.66	1488 / 3.33	1553 / 4.04					
8000	1428 / 2.38	1494 / 3.05	1557 / 3.75						

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 500 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 500 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 500 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 500 to 1580.