

# RTU4-E.1204-28-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3750				715 / 0.78	784 / 1.04	850 / 1.31	912 / 1.59	971 / 1.89	1027 / 2.20	1081 / 2.52	1133 / 2.85	1183 / 3.19	1231 / 3.53	1277 / 3.88
4275				758 / 0.91	821 / 1.19	882 / 1.48	940 / 1.78	996 / 2.10	1050 / 2.43	1102 / 2.77	1152 / 3.12	1200 / 3.48	1247 / 3.85	1292 / 4.22
4800			750 / 0.80	807 / 1.07	864 / 1.36	920 / 1.66	974 / 1.99	1027 / 2.33	1078 / 2.67	1127 / 3.04	1175 / 3.41	1222 / 3.79	1266 / 4.17	
5325	711 / 0.50	758 / 0.72	808 / 0.97	859 / 1.25	911 / 1.55	962 / 1.88	1013 / 2.22	1062 / 2.57	1110 / 2.94	1157 / 3.32	1203 / 3.71	1247 / 4.11	1291 / 4.52	
5850	781 / 0.66	823 / 0.90	868 / 1.17	915 / 1.47	962 / 1.78	1009 / 2.12	1056 / 2.48	1102 / 2.85	1147 / 3.24	1191 / 3.63	1234 / 4.04	1277 / 4.46		
6375	851 / 0.86	890 / 1.12	931 / 1.40	973 / 1.71	1016 / 2.05	1059 / 2.40	1102 / 2.77	1145 / 3.16	1187 / 3.56	1229 / 3.97	1270 / 4.40			
6900	921 / 1.09	957 / 1.37	994 / 1.67	1033 / 1.99	1072 / 2.34	1112 / 2.71	1152 / 3.10	1192 / 3.50	1231 / 3.92	1271 / 4.35				
7425	991 / 1.36	1024 / 1.65	1059 / 1.97	1094 / 2.32	1131 / 2.68	1167 / 3.06	1204 / 3.46	1242 / 3.88	1279 / 4.31					
7950	1061 / 1.67	1092 / 1.98	1124 / 2.32	1157 / 2.68	1191 / 3.06	1225 / 3.46	1259 / 3.87	1294 / 4.30						
8475	1131 / 2.02	1160 / 2.35	1190 / 2.71	1221 / 3.09	1252 / 3.48	1284 / 3.89								
9000	1201 / 2.42	1228 / 2.77	1256 / 3.15	1285 / 3.54										

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 700 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 700 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 700 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 700 to 1300.