

# RTU4-E.1206-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3750					1405 / 2.04	1514 / 2.55	1619 / 3.10	1721 / 3.67	1820 / 4.26
4025				1341 / 1.71	1446 / 2.21	1548 / 2.73	1649 / 3.30	1746 / 3.88	1841 / 4.49
4300				1391 / 1.88	1489 / 2.39	1587 / 2.93	1682 / 3.50	1775 / 4.11	1867 / 4.74
4575			1348 / 1.57	1443 / 2.06	1536 / 2.58	1628 / 3.14	1719 / 3.73	1808 / 4.35	
4850		1310 / 1.27	1406 / 1.75	1496 / 2.26	1585 / 2.80	1672 / 3.37	1759 / 3.98	1843 / 4.61	
5125		1375 / 1.44	1465 / 1.94	1552 / 2.47	1636 / 3.03	1719 / 3.62	1801 / 4.24		
5400	1343 / 1.12	1438 / 1.63	1525 / 2.15	1608 / 2.70	1689 / 3.28	1768 / 3.89	1846 / 4.52		
5675	1411 / 1.31	1503 / 1.84	1586 / 2.38	1665 / 2.95	1742 / 3.55	1818 / 4.17			
5950	1480 / 1.50	1567 / 2.06	1648 / 2.63	1724 / 3.22	1798 / 3.84				
6225	1548 / 1.72	1633 / 2.30	1710 / 2.90	1783 / 3.51	1854 / 4.15				
6500	1617 / 1.96	1698 / 2.57	1772 / 3.19	1843 / 3.82					

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 1300 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 1300 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 1300 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 1300 to 1870.