

RTU4-E.1504-22-FA

CFM	Static Pressure in Inches W.G.															
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500	3.750
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500									1523 / 2.53	1570 / 2.80	1616 / 3.08	1662 / 3.37	1708 / 3.67	1754 / 3.97	1799 / 4.29	1844 / 4.61
4700								1513 / 2.41	1558 / 2.68	1603 / 2.96	1648 / 3.25	1692 / 3.54	1736 / 3.84	1780 / 4.15	1824 / 4.47	1867 / 4.79
4900							1506 / 2.29	1550 / 2.56	1594 / 2.84	1637 / 3.12	1680 / 3.42	1724 / 3.72	1766 / 4.02	1808 / 4.34	1850 / 4.66	
5100						1504 / 2.18	1546 / 2.45	1589 / 2.72	1631 / 3.01	1673 / 3.30	1715 / 3.60	1756 / 3.90	1797 / 4.22	1838 / 4.54		
5300					1503 / 2.07	1546 / 2.34	1587 / 2.61	1628 / 2.90	1669 / 3.19	1710 / 3.48	1750 / 3.79	1790 / 4.10	1829 / 4.42	1869 / 4.75		
5500				1505 / 1.96	1547 / 2.23	1588 / 2.51	1629 / 2.79	1669 / 3.08	1708 / 3.38	1747 / 3.68	1786 / 3.99	1825 / 4.31	1863 / 4.63			
5700			1509 / 1.86	1551 / 2.13	1592 / 2.40	1631 / 2.69	1671 / 2.98	1709 / 3.27	1747 / 3.57	1786 / 3.89	1823 / 4.20	1861 / 4.53				
5900		1513 / 1.74	1556 / 2.02	1597 / 2.30	1637 / 2.58	1675 / 2.87	1713 / 3.17	1751 / 3.47	1788 / 3.78	1825 / 4.10	1861 / 4.42					
6100	1517 / 1.62	1561 / 1.91	1603 / 2.19	1643 / 2.48	1681 / 2.77	1719 / 3.07	1756 / 3.38	1793 / 3.69	1829 / 4.00	1864 / 4.33						
6300	1567 / 1.79	1610 / 2.08	1650 / 2.37	1689 / 2.67	1727 / 2.97	1763 / 3.28	1799 / 3.59	1835 / 3.91	1870 / 4.24							
6500	1617 / 1.96	1658 / 2.26	1698 / 2.57	1736 / 2.88	1772 / 3.19	1808 / 3.50	1843 / 3.82									

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 1500 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 1500 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 1500 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 1500 to 1870.