

RTU4-E.1506-22-FA

CFM	Static Pressure in Inches W.G.							
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500					1523 / 2.53	1616 / 3.08	1708 / 3.67	1799 / 4.29
4700					1558 / 2.68	1648 / 3.25	1736 / 3.84	1824 / 4.47
4900				1506 / 2.29	1594 / 2.84	1680 / 3.42	1766 / 4.02	1850 / 4.66
5100				1546 / 2.45	1631 / 3.01	1715 / 3.60	1797 / 4.22	
5300			1503 / 2.07	1587 / 2.61	1669 / 3.19	1750 / 3.79	1829 / 4.42	
5500			1547 / 2.23	1629 / 2.79	1708 / 3.38	1786 / 3.99	1863 / 4.63	
5700		1509 / 1.86	1592 / 2.40	1671 / 2.98	1747 / 3.57	1823 / 4.20		
5900		1556 / 2.02	1637 / 2.58	1713 / 3.17	1788 / 3.78	1861 / 4.42		
6100	1517 / 1.62	1603 / 2.19	1681 / 2.77	1756 / 3.38	1829 / 4.00			
6300	1567 / 1.79	1650 / 2.37	1727 / 2.97	1799 / 3.59	1870 / 4.24			
6500	1617 / 1.96	1698 / 2.57	1772 / 3.19	1843 / 3.82				

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 1500 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 1500 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 1500 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 1500 to 1870.