

RTU4-E.1506-28-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500							954 / 1.87	1009 / 2.19	1062 / 2.53	1112 / 2.88	1161 / 3.24	1209 / 3.61	1255 / 3.99	1299 / 4.37
4950						932 / 1.72	985 / 2.05	1036 / 2.39	1087 / 2.75	1135 / 3.11	1183 / 3.49	1229 / 3.88	1273 / 4.27	
5400					918 / 1.59	969 / 1.91	1019 / 2.25	1067 / 2.61	1115 / 2.98	1162 / 3.37	1207 / 3.76	1251 / 4.16	1294 / 4.57	
5850				915 / 1.47	962 / 1.78	1009 / 2.12	1056 / 2.48	1102 / 2.85	1147 / 3.24	1191 / 3.63	1234 / 4.04	1277 / 4.46		
6300			922 / 1.37	964 / 1.67	1008 / 2.01	1052 / 2.36	1095 / 2.72	1139 / 3.11	1181 / 3.51	1224 / 3.92	1265 / 4.35			
6750	901 / 1.02	938 / 1.29	976 / 1.59	1015 / 1.91	1056 / 2.25	1097 / 2.62	1138 / 3.00	1178 / 3.40	1218 / 3.81	1258 / 4.24	1298 / 4.68			
7200	961 / 1.24	995 / 1.53	1031 / 1.84	1068 / 2.17	1105 / 2.53	1143 / 2.91	1182 / 3.30	1220 / 3.71	1258 / 4.14	1296 / 4.58				
7650	1021 / 1.49	1053 / 1.79	1086 / 2.12	1121 / 2.47	1156 / 2.84	1192 / 3.22	1228 / 3.63	1264 / 4.06	1300 / 4.50					
8100	1081 / 1.76	1111 / 2.08	1143 / 2.43	1175 / 2.79	1208 / 3.17	1241 / 3.58	1275 / 3.99							
8550	1141 / 2.07	1170 / 2.41	1199 / 2.77	1230 / 3.15	1261 / 3.55	1292 / 3.96								
9000	1201 / 2.42	1228 / 2.77	1256 / 3.15	1285 / 3.54										

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 900 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 900 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 900 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 900 to 1300.