

RTU4-E.306-28-FA

| CFM | Static Pressure in Inches W.G. | | | | | | | | | | | | | | |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.250 | 0.500 | 0.750 | 1.000 | 1.250 | 1.500 | 1.750 | 2.000 | 2.250 | 2.500 | 2.750 | 3.000 | 3.250 | 3.500 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 1500 | | | | 609 / 0.40 | 698 / 0.56 | 777 / 0.72 | 849 / 0.89 | 916 / 1.07 | 977 / 1.26 | 1036 / 1.46 | 1091 / 1.66 | 1143 / 1.88 | 1194 / 2.11 | 1243 / 2.35 | 1289 / 2.59 |
| 2260 | | | | 628 / 0.51 | 715 / 0.72 | 793 / 0.95 | 864 / 1.18 | 929 / 1.41 | 990 / 1.64 | 1047 / 1.88 | 1102 / 2.12 | 1154 / 2.37 | 1203 / 2.62 | 1251 / 2.88 | 1297 / 3.14 |
| 3020 | | | | 663 / 0.60 | 741 / 0.84 | 815 / 1.11 | 883 / 1.39 | 946 / 1.69 | 1007 / 1.98 | 1063 / 2.29 | 1117 / 2.59 | 1168 / 2.90 | 1217 / 3.20 | 1265 / 3.52 | |
| 3780 | | | 647 / 0.56 | 716 / 0.76 | 784 / 0.99 | 849 / 1.27 | 912 / 1.57 | 972 / 1.90 | 1029 / 2.24 | 1084 / 2.59 | 1136 / 2.95 | 1186 / 3.32 | 1235 / 3.69 | 1281 / 4.07 | |
| 4540 | | 664 / 0.59 | 725 / 0.79 | 783 / 1.00 | 841 / 1.23 | 898 / 1.50 | 954 / 1.80 | 1008 / 2.12 | 1061 / 2.48 | 1112 / 2.85 | 1162 / 3.25 | 1210 / 3.65 | 1257 / 4.07 | | |
| 5300 | 697 / 0.50 | 755 / 0.84 | 809 / 1.09 | 860 / 1.33 | 910 / 1.57 | 960 / 1.83 | 1009 / 2.12 | 1057 / 2.44 | 1105 / 2.79 | 1152 / 3.17 | 1198 / 3.57 | 1243 / 3.98 | 1287 / 4.42 | | |
| 6060 | 797 / 0.75 | 849 / 1.15 | 896 / 1.46 | 942 / 1.73 | 987 / 2.00 | 1031 / 2.28 | 1074 / 2.57 | 1117 / 2.89 | 1160 / 3.23 | 1203 / 3.59 | 1245 / 3.99 | 1286 / 4.40 | | | |
| 6820 | 896 / 1.07 | 943 / 1.54 | 986 / 1.90 | 1028 / 2.23 | 1068 / 2.53 | 1108 / 2.83 | 1147 / 3.14 | 1186 / 3.46 | 1224 / 3.80 | 1263 / 4.17 | | | | | |
| 7580 | 996 / 1.47 | 1035 / 1.96 | 1079 / 2.43 | 1116 / 2.81 | 1153 / 3.16 | 1189 / 3.50 | 1225 / 3.83 | 1260 / 4.17 | 1296 / 4.52 | | | | | | |
| 8340 | 1096 / 1.95 | 1135 / 2.56 | 1172 / 3.05 | 1207 / 3.49 | 1241 / 3.89 | 1274 / 4.27 | | | | | | | | | |

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 600 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 600 to 1300.