

RTU4-E.454-28-FA

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500				609 / 0.40	698 / 0.56	777 / 0.72	849 / 0.89	916 / 1.07	977 / 1.26	1036 / 1.46	1091 / 1.66	1143 / 1.88	1194 / 2.11	1243 / 2.35	1289 / 2.59
2260				628 / 0.51	715 / 0.72	793 / 0.95	864 / 1.18	929 / 1.41	990 / 1.64	1047 / 1.88	1102 / 2.12	1154 / 2.37	1203 / 2.62	1251 / 2.88	1297 / 3.14
3020				663 / 0.60	741 / 0.84	815 / 1.11	883 / 1.39	946 / 1.69	1007 / 1.98	1063 / 2.29	1117 / 2.59	1168 / 2.90	1217 / 3.20	1265 / 3.52	
3780			647 / 0.56	716 / 0.76	784 / 0.99	849 / 1.27	912 / 1.57	972 / 1.90	1029 / 2.24	1084 / 2.59	1136 / 2.95	1186 / 3.32	1235 / 3.69	1281 / 4.07	
4540		664 / 0.59	725 / 0.79	783 / 1.00	841 / 1.23	898 / 1.50	954 / 1.80	1008 / 2.12	1061 / 2.48	1112 / 2.85	1162 / 3.25	1210 / 3.65	1257 / 4.07		
5300	697 / 0.50	755 / 0.84	809 / 1.09	860 / 1.33	910 / 1.57	960 / 1.83	1009 / 2.12	1057 / 2.44	1105 / 2.79	1152 / 3.17	1198 / 3.57	1243 / 3.98	1287 / 4.42		
6060	797 / 0.75	849 / 1.15	896 / 1.46	942 / 1.73	987 / 2.00	1031 / 2.28	1074 / 2.57	1117 / 2.89	1160 / 3.23	1203 / 3.59	1245 / 3.99	1286 / 4.40			
6820	896 / 1.07	943 / 1.54	986 / 1.90	1028 / 2.23	1068 / 2.53	1108 / 2.83	1147 / 3.14	1186 / 3.46	1224 / 3.80	1263 / 4.17					
7580	996 / 1.47	1035 / 1.96	1079 / 2.43	1116 / 2.81	1153 / 3.16	1189 / 3.50	1225 / 3.83	1260 / 4.17	1296 / 4.52						
8340	1096 / 1.95	1135 / 2.56	1172 / 3.05	1207 / 3.49	1241 / 3.89	1274 / 4.27									

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 600 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 600 to 1300.