

# RTU4-E.456-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			888 / 0.46	1073 / 0.74	1229 / 1.04	1366 / 1.37	1491 / 1.71	1604 / 2.07	1712 / 2.45	1812 / 2.83
2010		722 / 0.28	920 / 0.56	1096 / 0.89	1251 / 1.25	1388 / 1.63	1512 / 2.03	1626 / 2.43	1733 / 2.86	1834 / 3.31
2520		810 / 0.37	975 / 0.68	1132 / 1.05	1277 / 1.45	1411 / 1.88	1534 / 2.33	1648 / 2.80	1755 / 3.28	1854 / 3.77
3030	746 / 0.19	911 / 0.50	1051 / 0.84	1187 / 1.23	1318 / 1.67	1443 / 2.14	1561 / 2.64	1672 / 3.15	1777 / 3.69	
3540	871 / 0.30	1019 / 0.66	1142 / 1.04	1260 / 1.46	1376 / 1.92	1489 / 2.42	1599 / 2.95	1704 / 3.51	1805 / 4.09	
4050	997 / 0.45	1131 / 0.86	1241 / 1.28	1346 / 1.73	1449 / 2.22	1551 / 2.75	1650 / 3.30	1748 / 3.90	1843 / 4.51	
4560	1122 / 0.64	1245 / 1.11	1346 / 1.57	1441 / 2.05	1533 / 2.57	1625 / 3.13	1716 / 3.71	1805 / 4.33		
5070	1248 / 0.88	1361 / 1.40	1455 / 1.91	1542 / 2.44	1627 / 2.99	1709 / 3.57	1792 / 4.18			
5580	1373 / 1.17	1479 / 1.75	1567 / 2.31	1647 / 2.88	1725 / 3.47	1802 / 4.08				
6090	1499 / 1.52	1598 / 2.16	1680 / 2.77	1756 / 3.39	1829 / 4.01					

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 700 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 700 to 1870.