

RTU4-E.456-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500				930 / 0.75	1066 / 1.06	1189 / 1.39	1299 / 1.74	1401 / 2.11	1496 / 2.50
2160				951 / 0.96	1087 / 1.34	1207 / 1.74	1316 / 2.16	1415 / 2.59	1510 / 3.04
2820			835 / 0.74	981 / 1.16	1111 / 1.61	1229 / 2.08	1336 / 2.57	1437 / 3.08	1529 / 3.59
3480			898 / 0.92	1025 / 1.37	1145 / 1.88	1258 / 2.41	1362 / 2.97	1460 / 3.55	1551 / 4.14
4140		862 / 0.70	976 / 1.14	1087 / 1.63	1194 / 2.17	1297 / 2.76	1395 / 3.37	1489 / 4.01	1578 / 4.67
4800	844 / 0.47	963 / 0.94	1065 / 1.42	1162 / 1.95	1257 / 2.52	1350 / 3.14	1441 / 3.80	1528 / 4.49	
5460	960 / 0.69	1068 / 1.22	1160 / 1.76	1247 / 2.32	1332 / 2.94	1416 / 3.59	1498 / 4.29	1578 / 5.02	
6120	1076 / 0.97	1175 / 1.57	1259 / 2.16	1338 / 2.78	1415 / 3.43	1491 / 4.12	1566 / 4.85		
6780	1192 / 1.33	1283 / 1.99	1361 / 2.64	1434 / 3.30	1505 / 4.00	1574 / 4.73			
7440	1308 / 1.75	1392 / 2.48	1465 / 3.19	1534 / 3.92					

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.