

**RTU4-E.604-25-FA**

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000				945 / 0.91	1081 / 1.27	1202 / 1.66	1311 / 2.06	1412 / 2.47	1507 / 2.91
2600			820 / 0.69	969 / 1.09	1102 / 1.52	1220 / 1.96	1329 / 2.43	1429 / 2.91	1521 / 3.40
3200			870 / 0.84	1005 / 1.28	1130 / 1.76	1244 / 2.27	1350 / 2.80	1448 / 3.34	1541 / 3.90
3800		810 / 0.60	934 / 1.02	1054 / 1.50	1168 / 2.02	1276 / 2.58	1377 / 3.17	1472 / 3.77	1562 / 4.39
4400		901 / 0.79	1009 / 1.24	1115 / 1.75	1218 / 2.31	1318 / 2.91	1413 / 3.54	1504 / 4.20	
5000	893 / 0.58	995 / 1.02	1092 / 1.51	1186 / 2.05	1279 / 2.64	1370 / 3.28	1458 / 3.95	1543 / 4.65	
5600	1000 / 0.82	1092 / 1.30	1179 / 1.83	1264 / 2.40	1348 / 3.03	1431 / 3.70	1512 / 4.41		
6200	1107 / 1.11	1191 / 1.64	1270 / 2.21	1348 / 2.82	1425 / 3.48	1500 / 4.18	1575 / 4.92		
6800	1214 / 1.46	1291 / 2.04	1364 / 2.65	1436 / 3.31	1506 / 4.00	1576 / 4.74			
7400	1321 / 1.88	1392 / 2.51	1460 / 3.17	1526 / 3.86					
8000	1428 / 2.38	1494 / 3.05	1557 / 3.75						

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.