

RTU4-E.606-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000		721 / 0.27	920 / 0.56	1095 / 0.89	1249 / 1.24	1387 / 1.62	1512 / 2.02	1626 / 2.43	1733 / 2.86	1833 / 3.30
2450		797 / 0.35	967 / 0.67	1126 / 1.03	1273 / 1.42	1406 / 1.84	1530 / 2.29	1644 / 2.75	1750 / 3.22	1850 / 3.70
2900	721 / 0.17	884 / 0.46	1031 / 0.80	1172 / 1.19	1307 / 1.61	1434 / 2.07	1552 / 2.55	1665 / 3.06	1769 / 3.57	1870 / 4.11
3350	833 / 0.27	977 / 0.59	1106 / 0.96	1232 / 1.37	1354 / 1.83	1471 / 2.32	1583 / 2.83	1691 / 3.38	1793 / 3.94	
3800	945 / 0.39	1074 / 0.75	1190 / 1.15	1302 / 1.59	1412 / 2.07	1520 / 2.59	1625 / 3.13	1726 / 3.71	1823 / 4.30	
4250	1057 / 0.55	1175 / 0.95	1280 / 1.38	1382 / 1.85	1481 / 2.35	1579 / 2.89	1676 / 3.47	1770 / 4.07	1862 / 4.69	
4700	1169 / 0.74	1277 / 1.18	1374 / 1.65	1467 / 2.15	1558 / 2.68	1648 / 3.25	1736 / 3.84	1824 / 4.47		
5150	1281 / 0.98	1380 / 1.46	1471 / 1.96	1556 / 2.49	1641 / 3.05	1724 / 3.65	1805 / 4.27			
5600	1393 / 1.25	1485 / 1.78	1570 / 2.32	1649 / 2.88	1728 / 3.47	1805 / 4.10				
6050	1504 / 1.58	1591 / 2.15	1670 / 2.72	1746 / 3.33	1818 / 3.95					
6500	1617 / 1.96	1698 / 2.57	1772 / 3.19	1843 / 3.82						

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 700 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 700 to 1870.