

RTU4-E.904-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000				1184 / 1.22	1316 / 1.66	1441 / 2.12	1558 / 2.61	1669 / 3.13	1774 / 3.65
3350			1106 / 0.96	1232 / 1.37	1354 / 1.83	1471 / 2.32	1583 / 2.83	1691 / 3.38	1793 / 3.94
3700			1171 / 1.11	1286 / 1.54	1398 / 2.01	1508 / 2.52	1614 / 3.06	1717 / 3.63	1816 / 4.22
4050		1130 / 0.86	1240 / 1.27	1346 / 1.73	1450 / 2.22	1552 / 2.75	1652 / 3.31	1749 / 3.90	1843 / 4.52
4400		1208 / 1.02	1311 / 1.47	1409 / 1.94	1506 / 2.46	1601 / 3.01	1695 / 3.59	1787 / 4.20	
4750	1181 / 0.77	1288 / 1.21	1384 / 1.68	1477 / 2.18	1567 / 2.72	1656 / 3.29	1744 / 3.89	1830 / 4.52	
5100	1268 / 0.95	1369 / 1.43	1460 / 1.92	1546 / 2.45	1631 / 3.01	1715 / 3.60	1797 / 4.22		
5450	1355 / 1.16	1450 / 1.67	1536 / 2.19	1618 / 2.75	1698 / 3.33	1777 / 3.94	1855 / 4.58		
5800	1442 / 1.39	1532 / 1.94	1614 / 2.49	1692 / 3.07	1768 / 3.68	1842 / 4.31			
6150	1529 / 1.66	1615 / 2.24	1693 / 2.82	1767 / 3.43	1839 / 4.06				
6500	1617 / 1.96	1698 / 2.57	1772 / 3.19	1843 / 3.82					

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 1100 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 1100 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 1100 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 1100 to 1870.