

RTU4-E.904-28-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000				664 / 0.63	741 / 0.85	814 / 1.10	881 / 1.35	944 / 1.62	1003 / 1.90	1060 / 2.19	1114 / 2.48	1165 / 2.79	1215 / 3.10	1262 / 3.42
3600			629 / 0.52	704 / 0.75	775 / 1.00	841 / 1.26	905 / 1.54	965 / 1.84	1022 / 2.14	1076 / 2.45	1129 / 2.78	1178 / 3.10	1227 / 3.44	1273 / 3.79
4200		622 / 0.43	687 / 0.65	752 / 0.89	816 / 1.16	877 / 1.45	936 / 1.75	992 / 2.07	1047 / 2.40	1099 / 2.73	1149 / 3.08	1197 / 3.44	1244 / 3.80	1290 / 4.18
4800	641 / 0.37	693 / 0.57	750 / 0.80	807 / 1.07	864 / 1.36	920 / 1.66	974 / 1.99	1027 / 2.33	1078 / 2.67	1127 / 3.04	1175 / 3.41	1222 / 3.79	1266 / 4.17	
5400	721 / 0.52	767 / 0.75	816 / 1.00	867 / 1.28	918 / 1.59	969 / 1.91	1019 / 2.25	1067 / 2.61	1115 / 2.98	1162 / 3.37	1207 / 3.76	1251 / 4.16	1294 / 4.57	
6000	801 / 0.72	842 / 0.96	886 / 1.23	931 / 1.53	977 / 1.85	1023 / 2.20	1069 / 2.56	1114 / 2.93	1158 / 3.32	1202 / 3.73	1244 / 4.14	1286 / 4.57		
6600	881 / 0.95	918 / 1.22	958 / 1.51	998 / 1.83	1040 / 2.17	1081 / 2.53	1123 / 2.91	1165 / 3.30	1206 / 3.71	1246 / 4.13	1287 / 4.56			
7200	961 / 1.24	995 / 1.53	1031 / 1.84	1068 / 2.17	1105 / 2.53	1143 / 2.91	1182 / 3.30	1220 / 3.71	1258 / 4.14	1296 / 4.58				
7800	1041 / 1.58	1072 / 1.88	1105 / 2.22	1139 / 2.57	1173 / 2.94	1208 / 3.34	1243 / 3.75	1279 / 4.18						
8400	1121 / 1.97	1150 / 2.30	1180 / 2.65	1211 / 3.02	1243 / 3.42	1275 / 3.83								
9000	1201 / 2.42	1228 / 2.77	1256 / 3.15	1285 / 3.54										

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 600 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 600 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 600 to 1300.