

RTU4-I.200-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			902 / 0.48	1085 / 0.76	1240 / 1.07	1376 / 1.40	1500 / 1.75	1613 / 2.11	1720 / 2.49	1818 / 2.88
2010		749 / 0.31	944 / 0.60	1117 / 0.93	1269 / 1.29	1405 / 1.67	1527 / 2.07	1641 / 2.49	1746 / 2.92	1846 / 3.37
2520		844 / 0.43	1008 / 0.76	1162 / 1.13	1305 / 1.53	1437 / 1.97	1557 / 2.42	1670 / 2.88	1775 / 3.37	
3030	804 / 0.28	953 / 0.59	1091 / 0.95	1226 / 1.36	1356 / 1.81	1478 / 2.28	1594 / 2.78	1703 / 3.30	1807 / 3.83	
3540	938 / 0.45	1069 / 0.80	1189 / 1.20	1307 / 1.64	1422 / 2.12	1534 / 2.64	1641 / 3.18	1745 / 3.74	1844 / 4.32	
4050	1074 / 0.68	1189 / 1.07	1296 / 1.50	1400 / 1.98	1502 / 2.50	1603 / 3.05	1702 / 3.62	1798 / 4.23		
4560	1209 / 0.96	1313 / 1.40	1409 / 1.87	1502 / 2.39	1594 / 2.94	1685 / 3.52	1775 / 4.14	1864 / 4.78		
5070	1344 / 1.32	1438 / 1.80	1526 / 2.32	1611 / 2.87	1695 / 3.46	1777 / 4.08	1859 / 4.72			
5580	1479 / 1.77	1565 / 2.29	1646 / 2.85	1724 / 3.44	1801 / 4.06					
6090	1615 / 2.29	1694 / 2.86	1769 / 3.46	1841 / 4.09						
6600	1750 / 2.92	1823 / 3.53								

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 700 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 700 to 1870.