

RTU4-I.200-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500				939 / 0.77	1078 / 1.09	1200 / 1.43	1311 / 1.79	1414 / 2.16	1509 / 2.56
2160			818 / 0.65	969 / 1.01	1102 / 1.39	1221 / 1.79	1330 / 2.22	1430 / 2.65	1525 / 3.12
2820			877 / 0.85	1016 / 1.27	1140 / 1.72	1253 / 2.19	1358 / 2.68	1456 / 3.18	1548 / 3.70
3480		814 / 0.66	951 / 1.10	1076 / 1.58	1192 / 2.09	1299 / 2.62	1398 / 3.18	1492 / 3.75	
4140	810 / 0.53	920 / 0.92	1037 / 1.40	1149 / 1.94	1256 / 2.51	1355 / 3.11	1449 / 3.73	1538 / 4.37	
4800	939 / 0.83	1033 / 1.26	1133 / 1.78	1233 / 2.37	1330 / 3.00	1422 / 3.66	1510 / 4.34		
5460	1068 / 1.22	1150 / 1.69	1237 / 2.26	1326 / 2.89	1413 / 3.57	1498 / 4.29	1580 / 5.03		
6120	1197 / 1.72	1269 / 2.24	1346 / 2.84	1425 / 3.51	1504 / 4.24				
6780	1327 / 2.34	1391 / 2.90	1459 / 3.55	1530 / 4.26					
7440	1455 / 3.09	1514 / 3.70	1576 / 4.39						

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.