

RTU4-I.200-28-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			518 / 0.26	621 / 0.41	710 / 0.58	789 / 0.76	861 / 0.95	928 / 1.15	990 / 1.36	1048 / 1.58	1104 / 1.81	1157 / 2.05	1207 / 2.29	1254 / 2.54
2160		448 / 0.19	557 / 0.36	651 / 0.54	734 / 0.74	810 / 0.95	879 / 1.18	944 / 1.41	1005 / 1.65	1062 / 1.90	1117 / 2.17	1169 / 2.43	1219 / 2.71	1267 / 3.00
2820	424 / 0.14	519 / 0.30	612 / 0.49	695 / 0.70	771 / 0.93	842 / 1.17	907 / 1.43	969 / 1.69	1027 / 1.97	1083 / 2.25	1136 / 2.55	1187 / 2.85	1236 / 3.16	1282 / 3.47
3480	523 / 0.26	600 / 0.45	678 / 0.67	751 / 0.91	819 / 1.16	885 / 1.44	946 / 1.72	1005 / 2.02	1060 / 2.33	1113 / 2.64	1163 / 2.97	1213 / 3.30	1260 / 3.64	
4140	622 / 0.43	686 / 0.65	752 / 0.90	817 / 1.17	879 / 1.46	938 / 1.76	995 / 2.07	1049 / 2.40	1101 / 2.74	1151 / 3.08	1200 / 3.44	1246 / 3.80	1291 / 4.17	
4800	721 / 0.68	776 / 0.93	833 / 1.20	890 / 1.50	945 / 1.81	999 / 2.14	1051 / 2.49	1102 / 2.84	1151 / 3.21	1198 / 3.58	1243 / 3.97	1288 / 4.36		
5460	821 / 1.00	868 / 1.27	918 / 1.58	968 / 1.91	1018 / 2.25	1067 / 2.61	1115 / 2.98	1161 / 3.36	1207 / 3.76	1251 / 4.16	1294 / 4.57			
6120	920 / 1.40	962 / 1.71	1006 / 2.05	1050 / 2.39	1096 / 2.77	1140 / 3.16	1184 / 3.56	1227 / 3.97	1269 / 4.39					
6780	1019 / 1.91	1057 / 2.25	1096 / 2.61	1137 / 2.99	1177 / 3.39	1217 / 3.80	1257 / 4.23	1297 / 4.67						
7440	1118 / 2.52	1152 / 2.89	1188 / 3.28	1225 / 3.69	1261 / 4.12	1298 / 4.56								

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 400 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 400 to 1300.