

RTU4-I.300-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			896 / 0.47	1079 / 0.75	1235 / 1.06	1372 / 1.39	1496 / 1.73	1611 / 2.10	1716 / 2.47	1816 / 2.86
2000		735 / 0.29	933 / 0.58	1107 / 0.91	1259 / 1.27	1396 / 1.65	1520 / 2.04	1634 / 2.46	1741 / 2.89	1840 / 3.33
2500		825 / 0.40	991 / 0.72	1147 / 1.09	1291 / 1.49	1424 / 1.92	1544 / 2.36	1659 / 2.83	1764 / 3.31	1864 / 3.81
3000	774 / 0.24	927 / 0.54	1068 / 0.89	1205 / 1.29	1336 / 1.73	1460 / 2.20	1577 / 2.70	1687 / 3.21	1791 / 3.74	
3500	903 / 0.38	1037 / 0.72	1160 / 1.10	1279 / 1.54	1397 / 2.01	1510 / 2.51	1619 / 3.05	1723 / 3.60	1824 / 4.18	
4000	1032 / 0.56	1151 / 0.95	1260 / 1.37	1367 / 1.83	1471 / 2.34	1573 / 2.87	1674 / 3.44	1771 / 4.03	1866 / 4.65	
4500	1161 / 0.80	1268 / 1.23	1367 / 1.69	1462 / 2.19	1556 / 2.72	1649 / 3.29	1740 / 3.89	1830 / 4.51		
5000	1290 / 1.10	1387 / 1.57	1478 / 2.07	1564 / 2.61	1650 / 3.18	1734 / 3.77	1818 / 4.40			
5500	1419 / 1.46	1508 / 1.98	1591 / 2.52	1672 / 3.10	1750 / 3.70	1827 / 4.33				
6000	1548 / 1.90	1630 / 2.46	1707 / 3.04	1782 / 3.66	1855 / 4.30					
6500	1677 / 2.41	1753 / 3.02	1826 / 3.65							

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 700 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 700 to 1870.