

RTU4-I.300-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500				935 / 0.77	1073 / 1.08	1195 / 1.41	1304 / 1.76	1408 / 2.14	1503 / 2.53
2150			806 / 0.63	961 / 0.98	1095 / 1.36	1214 / 1.76	1323 / 2.18	1424 / 2.62	1518 / 3.07
2800			857 / 0.80	999 / 1.21	1126 / 1.66	1242 / 2.13	1347 / 2.61	1446 / 3.12	1538 / 3.64
3450			923 / 1.00	1051 / 1.47	1169 / 1.98	1278 / 2.51	1380 / 3.06	1476 / 3.63	1566 / 4.22
4100		888 / 0.80	1004 / 1.26	1117 / 1.78	1224 / 2.33	1326 / 2.92	1423 / 3.54	1514 / 4.18	
4750	895 / 0.67	994 / 1.09	1095 / 1.58	1194 / 2.14	1291 / 2.75	1385 / 3.39	1475 / 4.06	1561 / 4.75	
5400	1018 / 0.98	1104 / 1.45	1193 / 1.99	1281 / 2.58	1368 / 3.23	1454 / 3.92	1537 / 4.64		
6050	1140 / 1.38	1217 / 1.89	1296 / 2.47	1375 / 3.11	1454 / 3.80	1532 / 4.53			
6700	1262 / 1.87	1332 / 2.43	1403 / 3.06	1474 / 3.74	1546 / 4.47				
7350	1385 / 2.47	1448 / 3.08	1513 / 3.75	1578 / 4.47					
8000	1507 / 3.18	1566 / 3.84							

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.