

RTU4-I.300-28-FA

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			479 / 0.21	615 / 0.40	704 / 0.57	784 / 0.75	857 / 0.94	924 / 1.14	986 / 1.35	1045 / 1.57	1101 / 1.80	1153 / 2.03	1203 / 2.28	1251 / 2.53	1298 / 2.78
2150		431 / 0.17	543 / 0.33	638 / 0.51	723 / 0.71	800 / 0.92	870 / 1.14	935 / 1.37	997 / 1.62	1054 / 1.87	1109 / 2.12	1162 / 2.39	1212 / 2.67	1260 / 2.95	
2800	401 / 0.11	495 / 0.25	590 / 0.44	676 / 0.65	753 / 0.87	825 / 1.11	892 / 1.36	955 / 1.62	1014 / 1.89	1070 / 2.18	1124 / 2.47	1175 / 2.76	1224 / 3.07	1272 / 3.38	
3450	493 / 0.20	569 / 0.37	648 / 0.58	724 / 0.82	795 / 1.07	861 / 1.33	924 / 1.61	983 / 1.90	1039 / 2.20	1094 / 2.51	1145 / 2.83	1195 / 3.16	1242 / 3.50	1288 / 3.84	
4100	586 / 0.33	649 / 0.53	715 / 0.76	782 / 1.02	846 / 1.30	907 / 1.59	965 / 1.90	1020 / 2.22	1074 / 2.55	1125 / 2.89	1174 / 3.24	1222 / 3.59	1267 / 3.95		
4750	679 / 0.52	732 / 0.74	789 / 0.99	847 / 1.28	904 / 1.58	960 / 1.90	1013 / 2.23	1065 / 2.58	1115 / 2.94	1164 / 3.31	1210 / 3.68	1256 / 4.06	1300 / 4.46		
5400	772 / 0.76	818 / 1.01	868 / 1.28	918 / 1.59	969 / 1.92	1019 / 2.26	1069 / 2.62	1117 / 2.99	1164 / 3.38	1209 / 3.77	1253 / 4.18	1296 / 4.58			
6050	865 / 1.07	906 / 1.34	949 / 1.64	994 / 1.97	1040 / 2.32	1085 / 2.69	1130 / 3.07	1174 / 3.47	1218 / 3.88	1260 / 4.30					
6700	958 / 1.45	995 / 1.75	1033 / 2.07	1073 / 2.42	1114 / 2.80	1155 / 3.19	1196 / 3.59	1237 / 4.02	1277 / 4.45						
7350	1051 / 1.91	1084 / 2.24	1119 / 2.59	1155 / 2.96	1192 / 3.36	1229 / 3.77	1267 / 4.20								
8000	1144 / 2.47	1174 / 2.82	1206 / 3.19	1239 / 3.59	1272 / 4.01										

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 400 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 400 to 1300.