

RTU4-I.400-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900		715 / 0.27	920 / 0.55	1097 / 0.87	1251 / 1.22	1388 / 1.59	1513 / 1.97	1627 / 2.38	1734 / 2.80	1834 / 3.23
2360		792 / 0.35	967 / 0.66	1129 / 1.02	1276 / 1.41	1411 / 1.83	1533 / 2.26	1648 / 2.71	1753 / 3.17	1854 / 3.66
2820	719 / 0.18	882 / 0.47	1032 / 0.81	1175 / 1.19	1312 / 1.62	1440 / 2.07	1559 / 2.55	1671 / 3.05	1776 / 3.56	
3280	836 / 0.29	979 / 0.61	1110 / 0.98	1237 / 1.39	1360 / 1.85	1479 / 2.34	1592 / 2.86	1699 / 3.39	1802 / 3.95	
3740	953 / 0.43	1081 / 0.79	1198 / 1.19	1311 / 1.63	1422 / 2.12	1530 / 2.63	1635 / 3.18	1736 / 3.75	1834 / 4.35	
4200	1071 / 0.61	1186 / 1.01	1292 / 1.45	1393 / 1.92	1494 / 2.43	1592 / 2.97	1689 / 3.55	1783 / 4.15		
4660	1188 / 0.83	1293 / 1.27	1390 / 1.75	1483 / 2.25	1574 / 2.79	1664 / 3.36	1753 / 3.96	1840 / 4.60		
5120	1305 / 1.10	1402 / 1.59	1491 / 2.09	1577 / 2.63	1661 / 3.20	1743 / 3.80	1825 / 4.43			
5580	1422 / 1.43	1512 / 1.95	1595 / 2.50	1674 / 3.07	1752 / 3.67	1829 / 4.31				
6040	1539 / 1.81	1623 / 2.38	1700 / 2.96	1775 / 3.57	1848 / 4.21					
6500	1656 / 2.26	1735 / 2.87	1808 / 3.49							

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 700 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 700 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 700 to 1870.