

RTU4-I.400-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900				947 / 0.89	1083 / 1.24	1204 / 1.62	1314 / 2.01	1415 / 2.42	1508 / 2.84
2510			826 / 0.70	975 / 1.09	1107 / 1.51	1224 / 1.95	1332 / 2.40	1433 / 2.88	1526 / 3.37
3120			879 / 0.87	1015 / 1.31	1139 / 1.78	1253 / 2.29	1357 / 2.80	1455 / 3.34	1547 / 3.89
3730		820 / 0.64	946 / 1.07	1068 / 1.55	1182 / 2.08	1289 / 2.64	1389 / 3.22	1484 / 3.81	1573 / 4.43
4340	804 / 0.46	915 / 0.86	1025 / 1.32	1132 / 1.84	1236 / 2.41	1335 / 3.02	1430 / 3.65	1520 / 4.31	
4950	917 / 0.69	1014 / 1.12	1111 / 1.63	1207 / 2.18	1301 / 2.79	1392 / 3.44	1480 / 4.12	1564 / 4.83	
5560	1030 / 0.98	1117 / 1.46	1203 / 2.00	1289 / 2.59	1374 / 3.24	1457 / 3.93	1538 / 4.65		
6170	1143 / 1.33	1221 / 1.86	1299 / 2.44	1377 / 3.08	1454 / 3.76	1530 / 4.48			
6780	1256 / 1.77	1327 / 2.34	1398 / 2.97	1469 / 3.64	1540 / 4.36				
7390	1369 / 2.29	1434 / 2.91	1500 / 3.58	1565 / 4.30					
8000	1482 / 2.91	1542 / 3.58							

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.