

RTU4-I.400-28-FA

CFM	Static Pressure in Inches W.G.													
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1900		405 / 0.14	524 / 0.29	624 / 0.46	711 / 0.64	789 / 0.84	861 / 1.05	927 / 1.27	990 / 1.50	1048 / 1.74	1103 / 1.99	1156 / 2.24	1206 / 2.51	1255 / 2.78
2510		457 / 0.20	560 / 0.38	651 / 0.57	733 / 0.78	807 / 1.00	876 / 1.24	940 / 1.49	1001 / 1.75	1058 / 2.01	1113 / 2.29	1165 / 2.57	1215 / 2.87	1263 / 3.17
3120	436 / 0.13	520 / 0.29	608 / 0.48	689 / 0.70	764 / 0.94	834 / 1.19	899 / 1.45	961 / 1.73	1019 / 2.01	1074 / 2.30	1128 / 2.61	1178 / 2.92	1227 / 3.24	1274 / 3.56
3730	521 / 0.22	591 / 0.40	664 / 0.62	736 / 0.86	805 / 1.12	869 / 1.39	931 / 1.68	989 / 1.98	1044 / 2.29	1097 / 2.62	1148 / 2.95	1197 / 3.28	1245 / 3.63	1291 / 3.98
4340	606 / 0.35	665 / 0.55	728 / 0.78	791 / 1.05	853 / 1.33	912 / 1.63	969 / 1.95	1024 / 2.27	1077 / 2.61	1127 / 2.96	1176 / 3.31	1223 / 3.68	1269 / 4.05	
4950	692 / 0.52	743 / 0.74	797 / 1.00	853 / 1.28	908 / 1.59	962 / 1.91	1015 / 2.25	1066 / 2.60	1115 / 2.96	1162 / 3.33	1209 / 3.71	1254 / 4.11	1298 / 4.50	
5560	777 / 0.74	822 / 0.98	870 / 1.26	919 / 1.56	968 / 1.89	1018 / 2.23	1066 / 2.59	1113 / 2.97	1160 / 3.35	1205 / 3.75	1249 / 4.16	1291 / 4.57		
6170	862 / 1.01	902 / 1.28	945 / 1.57	989 / 1.90	1034 / 2.24	1078 / 2.61	1122 / 2.99	1166 / 3.38	1209 / 3.79	1252 / 4.22	1293 / 4.65			
6780	947 / 1.34	984 / 1.63	1022 / 1.95	1062 / 2.29	1102 / 2.65	1143 / 3.04	1183 / 3.44	1224 / 3.86	1264 / 4.29					
7390	1032 / 1.74	1066 / 2.05	1101 / 2.39	1137 / 2.75	1173 / 3.14	1210 / 3.54	1247 / 3.96	1285 / 4.40						
8000	1117 / 2.20	1148 / 2.54	1180 / 2.90	1213 / 3.29	1247 / 3.69	1281 / 4.11								

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.

Motor 186734/A01-ECM-50-480-28 has an rpm range of 400 to 1300.

Motor 186734/A01-ECM-60-480-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-50-240-28 has an rpm range of 400 to 1300.

Motor 186737/A01-ECM-60-240-28 has an rpm range of 400 to 1300.