

RTU4-I.500-22-FA

CFM	Static Pressure in Inches W.G.									
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000	4.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2300			956 / 0.64	1121 / 0.99	1270 / 1.38	1405 / 1.79	1528 / 2.21	1643 / 2.66	1749 / 3.12	1849 / 3.59
2720			1012 / 0.76	1160 / 1.14	1299 / 1.56	1429 / 2.00	1550 / 2.48	1662 / 2.96	1767 / 3.46	1867 / 3.98
3140		944 / 0.55	1077 / 0.90	1212 / 1.31	1339 / 1.76	1461 / 2.24	1576 / 2.74	1685 / 3.26	1789 / 3.81	
3560		1034 / 0.70	1156 / 1.08	1275 / 1.51	1390 / 1.98	1503 / 2.49	1612 / 3.02	1715 / 3.58	1815 / 4.16	
3980	1006 / 0.49	1128 / 0.87	1239 / 1.29	1346 / 1.74	1451 / 2.24	1554 / 2.77	1655 / 3.33	1753 / 3.92	1849 / 4.53	
4400	1112 / 0.67	1224 / 1.09	1326 / 1.53	1423 / 2.01	1520 / 2.53	1615 / 3.09	1708 / 3.67	1800 / 4.29		
4820	1218 / 0.88	1322 / 1.33	1416 / 1.81	1506 / 2.33	1595 / 2.87	1682 / 3.45	1769 / 4.06	1854 / 4.70		
5240	1324 / 1.13	1420 / 1.62	1508 / 2.14	1592 / 2.68	1660 / 3.15	1756 / 3.86	1836 / 4.49			
5660	1430 / 1.42	1520 / 1.95	1602 / 2.50	1682 / 3.08	1758 / 3.68	1834 / 4.31				
6080	1536 / 1.76	1620 / 2.33	1698 / 2.92	1773 / 3.53	1845 / 4.16					
6500	1642 / 2.15	1722 / 2.76	1795 / 3.38	1866 / 4.03						

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 900 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 900 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 900 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 900 to 1870.