

# RTU4-I.500-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2300			808 / 0.65	961 / 1.01	1095 / 1.41	1214 / 1.82	1323 / 2.26	1424 / 2.71	1518 / 3.18
2870			850 / 0.78	992 / 1.20	1120 / 1.65	1237 / 2.13	1343 / 2.62	1442 / 3.13	1535 / 3.66
3440			906 / 0.95	1035 / 1.41	1154 / 1.91	1265 / 2.44	1368 / 2.99	1465 / 3.56	1556 / 4.15
4010		855 / 0.71	974 / 1.15	1088 / 1.64	1198 / 2.19	1302 / 2.77	1400 / 3.37	1493 / 4.00	
4580	838 / 0.51	945 / 0.92	1049 / 1.39	1152 / 1.92	1251 / 2.50	1347 / 3.12	1440 / 3.77	1529 / 4.44	
5150	942 / 0.72	1038 / 1.18	1131 / 1.68	1223 / 2.25	1313 / 2.86	1402 / 3.52	1488 / 4.20	1572 / 4.92	
5720	1046 / 0.99	1133 / 1.49	1217 / 2.03	1301 / 2.63	1383 / 3.28	1464 / 3.97	1544 / 4.69		
6290	1151 / 1.32	1229 / 1.86	1307 / 2.45	1383 / 3.08	1458 / 3.76	1533 / 4.48			
6860	1255 / 1.71	1327 / 2.30	1398 / 2.92	1468 / 3.59	1538 / 4.31				
7430	1359 / 2.18	1426 / 2.80	1492 / 3.47	1557 / 4.18					
8000	1463 / 2.72	1526 / 3.39							

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.