

RTU4-I.600-22-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000		911 / 0.50	1053 / 0.85	1190 / 1.24	1322 / 1.68	1446 / 2.15	1564 / 2.64	1675 / 3.15	1779 / 3.68
3350		985 / 0.61	1114 / 0.98	1239 / 1.40	1360 / 1.85	1478 / 2.34	1590 / 2.86	1697 / 3.41	1799 / 3.97
3700	931 / 0.39	1061 / 0.74	1179 / 1.13	1294 / 1.57	1406 / 2.05	1516 / 2.56	1621 / 3.10	1724 / 3.67	1823 / 4.26
4050	1019 / 0.51	1140 / 0.89	1249 / 1.31	1355 / 1.77	1458 / 2.27	1560 / 2.80	1660 / 3.36	1757 / 3.95	1851 / 4.57
4400	1107 / 0.65	1219 / 1.07	1321 / 1.51	1419 / 1.99	1516 / 2.51	1611 / 3.06	1704 / 3.65	1796 / 4.26	
4750	1195 / 0.82	1300 / 1.27	1395 / 1.74	1487 / 2.24	1577 / 2.78	1666 / 3.36	1753 / 3.96	1840 / 4.59	
5100	1283 / 1.01	1382 / 1.49	1472 / 1.99	1558 / 2.52	1643 / 3.09	1726 / 3.68	1808 / 4.30		
5450	1371 / 1.23	1464 / 1.75	1549 / 2.28	1631 / 2.83	1710 / 3.42	1789 / 4.04	1866 / 4.68		
5800	1459 / 1.49	1547 / 2.03	1628 / 2.59	1705 / 3.18	1781 / 3.79	1855 / 4.43			
6150	1546 / 1.77	1630 / 2.35	1707 / 2.94	1781 / 3.55	1853 / 4.19				
6500	1634 / 2.09	1714 / 2.70	1788 / 3.32	1859 / 3.96					

Max Sizeable RPM = 1870 RPM. Table shown extended beyond this point for reference only.

Motor 186729/A01-ECM-50-480-22 has an rpm range of 900 to 1870.

Motor 186729/A01-ECM-60-480-22 has an rpm range of 900 to 1870.

Motor 186732/A01-ECM-50-240-22 has an rpm range of 900 to 1870.

Motor 186732/A01-ECM-60-240-22 has an rpm range of 900 to 1870.