

RTU4-I.600-25-FA

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000			858 / 0.81	998 / 1.24	1125 / 1.70	1240 / 2.19	1346 / 2.70	1445 / 3.22	1538 / 3.76
3500			909 / 0.95	1036 / 1.42	1155 / 1.92	1265 / 2.46	1368 / 3.01	1465 / 3.59	1556 / 4.18
4000		850 / 0.69	968 / 1.12	1083 / 1.62	1193 / 2.16	1297 / 2.73	1396 / 3.34	1490 / 3.97	1579 / 4.61
4500	817 / 0.47	927 / 0.87	1034 / 1.33	1138 / 1.85	1239 / 2.43	1336 / 3.04	1429 / 3.68	1519 / 4.35	
5000	908 / 0.64	1007 / 1.08	1104 / 1.57	1198 / 2.12	1291 / 2.72	1382 / 3.37	1469 / 4.04	1554 / 4.75	
5500	999 / 0.85	1090 / 1.32	1178 / 1.85	1264 / 2.44	1350 / 3.06	1433 / 3.73	1516 / 4.44		
6000	1089 / 1.10	1173 / 1.62	1254 / 2.18	1334 / 2.79	1410 / 3.42	1491 / 4.15	1568 / 4.89		
6500	1180 / 1.40	1258 / 1.96	1333 / 2.55	1407 / 3.20	1480 / 3.88	1553 / 4.61			
7000	1271 / 1.75	1343 / 2.34	1413 / 2.98	1482 / 3.65	1551 / 4.37				
7500	1362 / 2.15	1429 / 2.78	1495 / 3.46	1560 / 4.17					
8000	1452 / 2.61	1516 / 3.28	1578 / 3.99						

Max Sizeable RPM = 1580 RPM. Table shown extended beyond this point for reference only.

Motor 186736/A01-ECM-50-480-25 has an rpm range of 800 to 1580.

Motor 186736/A01-ECM-60-480-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-50-240-25 has an rpm range of 800 to 1580.

Motor 186738/A01-ECM-60-240-25 has an rpm range of 800 to 1580.